



## **Aba Daba Rents**

4351 Auburn Blvd.  
Sacramento, CA 95841-4152  
(916) 484-7368 Fax (916) 482-2552  
www.abadaba.com

### **PRESSURE WASHER, COLD WATER OPERATING INSTRUCTIONS**

#### **IMPORTANT!**

Read and Understand These Operating Instructions Before Operating the Machine

Pressure Washers operate at pressures ranging from 1000 to 5000 Per Square Inch (PSI). Failure to observe these warnings could result in serious personal injury. Operate this equipment only after reading and understanding ALL instructions! If you experience any problems, contact us immediately.

#### **DO NOT ATTEMPT ADJUSTMENTS OR REPAIRS YOURSELF! OPERATING A HIGH PRESSURE WASHER**

1. Check fuel tank and fill with proper fuel. Check oil level in engine and pump. Fill if necessary. Open fuel valve.
2. Attach any accessories to be used. (Check with the store about accessories available and instructions for use.)
3. Connect high pressure hose to the machine and gun valve with quick couplers. Make sure that locking sleeves are in the "LOCKED" position. Failure to properly lock quick coupler sleeves will result in blowing out the quick coupler o-ring seal. Excessive leaking will occur if quick coupler o-ring is missing.
4. Attach a standard garden hose (minimum 3/4" I.D.) to the machine and turn on water supply. **DO NOT** use a shallow lawn sprinkling well as a source!
5. With cleaning nozzle removed from the gun valve extension, squeeze gun valve trigger and hold open until a smooth flow of water appears. Then close trigger.
6. Start machine. Let it run for 3 minutes without load to warm up.
7. Select desired cleaning nozzle or accessory, and insert into extension quick coupler, making sure locking sleeve is in the "LOCKED" position.
8. Machine is ready for operation. **DO NOT** leave gun valve in a closed position for longer than 5 minutes with machine running. Stop machine to avoid overheating pump.
9. After cleaning job is finished, allow machine to run for one minute without load. Then stop the machine, and turn off the fuel valve. Turn off water at source and open gun valve to release system pressure **BEFORE** disconnecting hoses.

**WARNING! THIS ITEM CONTAINS ONE OR MORE CHEMICALS KNOWN  
TO THE STATE OF CALIFORNIA TO CAUSE  
CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.**